



Technical Data Sheet: CR90718

Product manual	<p>CR90718 is a polyurethane acrylate oligomer; it has the characteristics of fast curing speed, good yellowing resistance, good adhesion, good plating performance, good leveling and fullness, and high gloss. It is widely used in plastic coatings, vacuum plating primer, adhesives, inks and other fields.</p>	
Product features	<p>Fast curing speed</p> <p>Good yellowing resistance</p> <p>Good adhesion</p> <p>Good leveling and fullness</p> <p>Good plating</p>	
Recommended use	<p>Coatings</p> <p>Adhesives</p> <p>Inks</p>	
Specifications	<p>Functionality (theoretical)</p> <p>Appearance(By vision)</p> <p>Viscosity (CPS/60℃)</p> <p>Color(APHA)</p> <p>Efficient content(%)</p>	<p>2</p> <p>Clear liquid</p> <p>450-1600</p> <p>≤100</p> <p>100</p>
Packing	<p>Net weight 50KG plastic bucket and net weight 200KG iron drum</p>	
Storage conditions	<p>Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.</p>	
Use matters	<p>Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.</p>	