



Technical Data Sheet: HP6228

Product manual HP6228 is an aliphatic urethane acrylate oligomer. HP6228 was developed for UV curable coating and ink applications, where adhesion and weathering resistance are required. HP6228 demonstrates excellent weathering properties.

Product features

- Abrasion Resistance
- Adhesion
- Chemical Resistance
- Flexibility
- Heat Resistance
- Impact Strength
- Low Shrinkage
- Water Resistance
- Weatherability
- Fast cure speed

Recommended use

- Coatings
- Coatings, floor
- Coatings, metal
- Coatings, paper
- Inks

Specifications	Functionality (theoretical)	2
	Appearance(By vision)	Clear liquid
	Viscosity (CPS/60℃)	2000-6000
	Color(GAPHA)	≤100
	Efficient content(%)	100

Packing Net weight 50KG plastic bucket and net weight 200KG iron drum

Storage conditions Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.

Use matters Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.