



Technical Data Sheet: HP6615

Product manual	<p>HP6615 is a urethane acrylate oligomer that defers superior physical properties such as curing speed fast, surface-dry easily, non-yellowing, good gloss retention, good anti-cracking performance, good adhesion. Compared to similar products on the market, significant feature is high hardness, distinct low viscosity, good abrasion resistance, smell small and non-yellowing.</p>	
Product features	<p>Chemical Resistance</p> <p>Good hardness.</p> <p>Water Resistance</p> <p>Fast cure speed</p>	
Recommended use	<p>Coatings</p> <p>Inks</p>	
Specifications	<p>Functionality (theoretical)</p> <p>Appearance(By vision)</p> <p>Viscosity (CPS/25℃)</p> <p>Color(Gardner)</p> <p>Efficient content(%)</p>	<p>6</p> <p>Clear liquid</p> <p>8000-32000</p> <p>≤1</p> <p>100</p>
Packing	<p>Net weight 50KG plastic bucket and net weight 200KG iron drum</p>	
Storage conditions	<p>Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 °C, storage conditions under normal conditions for at least 6 months.</p>	
Use matters	<p>Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.</p>	