



# Technical Data Sheet: CR90145

**Product manual**      **CR90145** is a polyurethane acrylate oligomer ; It has fast curing speed, high solid content and low viscosity, good substrate wetting, good abrasion and scratch resistance, and good leveling and fullness; It is especially suitable for spraying varnish, plastic varnish, and wood coating.

**Product features**

- Fast curing speed
- Good substrate wetting
- Good abrasion and scratch resistance
- Good leveling and fullness
- Good yellow resistance

**Recommended use**

- Plastic coatings
- Wood Coatings
- OPV

<b>Specifications</b>	Functionality (theoretical)	6
	Appearance(By vision)	Clear liquid
	Viscosity (CPS/25℃)	300-1100
	Color(APHA)	≤100
	Efficient content(%)	100

**Packing**      Net weight 50KG plastic bucket and net weight 200KG iron drum.

**Storage conditions**      Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 °C, storage conditions under normal conditions for at least 6 months.

**Use matters**

Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.