



Technical Data Sheet: CR90156

Product manual	CR90156 is a polyester acrylate oligomer, it has good wetting to substrat ,fast curing speed,good flexibility and good yellow resistance.It is suitable used on wood coating ,screen ink,offset ink and all kinds of UV varnish.	
Product features	Fast curing speed Good wetting to substrat Good yellow resistance Good pigment wetting	
Suggested application	Inks(screen,offset,flexo) Wood coating OPV	
Specifications	Functional basis (theoretical)	2
	Appearance(By vision)	Little yellow liquid
	Viscosity(CPS/25°C)	16000-42000
	Color (Gardner)	≤ 6
	Efficient content(%)	100
Packing	Net weight 50KG plastic bucket and net weight 200KG iron drum.	
Storage conditions	Store product indoors at temperatures greater than product's freezing point (or greater than 0C/32F if no freezing point available) and below 38C/100F. Avoid prolonged (longer than shelf-life) storage temperatures above 38C/100F. Store in tightly closed containers in a properly vented storage area away from: heat, sparks, open flame, strong oxidizers, radiation, and other initiators. Prevent contamination by foreign materials. Prevent moisture contact. Use only non-sparking tools and limit storage time. Unless specified elsewhere, shelf-life is 6 months from receipt.	
Use matters	Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.	