



Technical Data Sheet: CR90475

Product manual	CR90475 is a tri-functional polyester acrylate oligomer with the characteristics of good yellowing resistance, excellent substrate wettability, and easy matting. It is especially suitable for wood coatings, plastic coatings	
Product features	<p>Good yellowing and weather resistance</p> <p>Good leveling, good wetting</p> <p>Low viscosity</p> <p>Easy to matting</p>	
Recommended use	<p>Plastic coatings</p> <p>Wood Coatings</p>	
Specifications	Functionality (theoretical)	3
	Appearance(By vision)	Clear liquid
	Viscosity (CPS/25℃)	60-200
	Color(Gardner)	≤2
	Efficient content(%)	100
Packing	Net weight 50KG plastic bucket and net weight 200KG iron drum	
Storage conditions	<p>Please keep cool or dry place, and avoid sun and heat;</p> <p>Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.</p>	
Use matters	<p>Avoid touching the skin and clothing, wear protective gloves when handling;</p> <p>Leak with a cloth when the leak, and wash with ethyl acetate;</p> <p>for details, please refer to the Material Safety Instructions (MSDS);</p> <p>Each batch of goods to be tested before they can be put into production.</p>	