



## Technical Data Sheet: CR90770

<b>Product manual</b>	<b>CR90770</b> is a three-body polyurethane acrylate ;It has self-matting property , good wetting,good flexibility ,less irritancy and delicate hand feeling.It is suitable for UV matting coating on plastic,wood ,paper and so on.										
<b>Product features</b>	High matting efficiency Fast curing speed Good wetting on substrate Good scratch resistance										
<b>Recommended use</b>	UV plastic coating UV wood coating OPV										
<b>Specifications</b>	<table><tr><td>Functional basis (theoretical)</td><td>3</td></tr><tr><td>Appearance(By vision)</td><td>Little yellow liquid</td></tr><tr><td>Viscosity (CPS/25℃)</td><td>200-900</td></tr><tr><td>Color(Gardner)</td><td>≤ 2</td></tr><tr><td>Efficient content(%)</td><td>100</td></tr></table>	Functional basis (theoretical)	3	Appearance(By vision)	Little yellow liquid	Viscosity (CPS/25℃)	200-900	Color(Gardner)	≤ 2	Efficient content(%)	100
Functional basis (theoretical)	3										
Appearance(By vision)	Little yellow liquid										
Viscosity (CPS/25℃)	200-900										
Color(Gardner)	≤ 2										
Efficient content(%)	100										
<b>Packing</b>	Net weight 50KG plastic bucket and net weight 200KG iron drum.										
<b>Storage conditions</b>	Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.										
<b>Use matters</b>	Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.										