



# Technical Data Sheet: CR91607

**Product manual**      **CR91607** is a modified epoxy acrylate resin; it has the characteristics of fast curing speed, good toughness, low odor, good yellowing resistance, good adhesion, and cost-effective. It is especially suitable for various coatings such as UV wood coating, plastic spray varnish, UV nail polish, screen ink and so on.

**Product features**

- Fast curing speed
- Good toughness
- Good yellowing resistance

**Recommended use**

- Wood Coatings
- Plastic coating
- Screen ink
- Vacuum plating primer

<b>Specifications</b>	Functionality (theoretical)	2
	Appearance(By vision)	Clear liquid
	Viscosity (CPS/60℃)	1500-3000
	Color(Gardner)	≤2
	Efficient content(%)	100

**Packing**      Net weight 50KG plastic bucket and net weight 200KG iron drum

**Storage conditions**      Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.

**Use matters**

Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.