



Technical Data Sheet: HT7401

Product manual **HT7401** is a four-functional polyester acrylate; it is a resin with low viscosity as monomer. It has good leveling and wettability, good yellowing resistance, good water resistance, high temperature resistance and other characteristics. It can solve pitting and pinholes efficiently, and it is suitable for automotive interior decoration and large-area construction; various solvent-free spraying, roller coating, curtain coating, and UV inks and other applications.

Product features

- Low odor and halogen-free
- Good wettability to various substrates without irritation
- Good leveling, high hardness
- Good yellowing resistance, good water resistance

Recommended use

- Automotive interior
- Plastic large area coating
- Woodware solvent-free spraying, roller coating, curtain coating
- Ink

Specifications	Functionality (theoretical)	4
	Appearance(By vision)	Clear liquid
	Viscosity (CPS/25℃)	100-500
	Color(APHA)	≤250
	Acid Value (mgKOH/g)	≤15
	Efficient content(%)	100

Packing Net weight 50KG plastic bucket and net weight 200KG iron drum.

Storage conditions Please keep cool or dry place, and avoid sun and heat;
Storage temperature does not exceed 40 °C, storage conditions under normal conditions for at least 6 months.

Use matters

Avoid touching the skin and clothing, wear protective gloves when handling;
Leak with a cloth when the leak, and wash with ethyl acetate;
for details, please refer to the Material Safety Instructions (MSDS);
Each batch of goods to be tested before they can be put into production.