



Technical Data Sheet: HT7602

Product manual

HT7602 is a 8-functional polyester acrylate, that with low viscosity, mirror leveling, high fullness, good wettability to various substrates, good yellowing resistance, good water resistance, good heat resistance and can effectively prevent problems such as pitting and pinholes are especially suitable for large area coatings, wood coatings, inks and other application fields.

Product features

Good wettability to various substrates
Mirror leveling and high fullness
Good toughness
Good yellowing resistance
Good water resistance
Friendly odor application

Recommended use

Plastic large area coating
Wood coatings
Inks

Specifications

Functionality (theoretical)	6
Appearance(By vision)	Clear liquid
Viscosity (CPS/25℃)	800-3200
Color(APHA)	≤300
Efficient content(%)	100

Packing

Net weight 50KG plastic bucket and net weight 200KG iron drum

Storage conditions

Please keep cool or dry place, and avoid sun and heat;
Storage temperature does not exceed 40 °C, storage conditions under normal conditions for at least 6 months.

Use matters

Avoid touching the skin and clothing, wear protective gloves when handling;
Leak with a cloth when the leak, and wash with ethyl acetate;
for details, please refer to the Material Safety Instructions (MSDS);
Each batch of goods to be tested before they can be put into production.