



Technical Data Sheet: HW6482

Product manual **HW6482** is a waterborne aliphatic urethane acrylate dispersion, which has the characteristics of fast curing speed, good adhesion, high hardness, good yellowing resistance, high gloss and good silver arrangement. It is especially suitable for UV waterborne coatings such as plastic high gloss / matte coating, wood coating, spray coating of silver on plastic, vacuum plating primer and other coatings.

Product features

- Fast curing speed
- Good flexibility
- High level & fullness
- Good silver powder arrangement

Recommended use

- Waterborne plastic coatings
- Waterborne wood coatings
- Waterborne vacuum electroplating primer

Specifications	Functionality (theoretical)	4
	Appearance(By vision)	Milky white liquid
	Viscosity (CPS/25℃)	≤300
	Efficient content(%)	40 ± 1

Packing Net weight 50KG plastic bucket and net weight 200KG plastic bucket.

Storage conditions Please keep cool or dry place, and avoid sun and heat;
Storage temperature does not exceed 40 °C, storage conditions under normal conditions for at least 6 months.

Use matters

Avoid touching the skin and clothing, wear protective gloves when handling;
Leak with a cloth when the leak, and wash with water;
for details, please refer to the Material Safety Instructions (MSDS);
Each batch of goods to be tested before they can be put into production.