



# Technical Data Sheet: SU322

<b>Product manual</b>	<p><b>SU322</b> is a epoxy acrylate oligomer. It has high reactivity and good flexibility. It is suggested in the outer protective coating of 3C products, wood coatings and so on. and is especially suitable for mobile phone, computer, cosmetics packaging, etc.</p>	
<b>Product features</b>	<p>Fast curing speed</p> <p>Good leveling and fullness</p> <p>Good water resistance</p> <p>Effectively prevent pitting</p>	
<b>Recommended use</b>	<p>Plastic coatings</p> <p>Wood coatings</p>	
<b>Specifications</b>	<p>Functionality (theoretical)</p> <p>Appearance(By vision)</p> <p>Viscosity (CPS/60℃)</p> <p>Color(Gardner)</p> <p>Efficient content(%)</p> <p>Acid value(mgKOH/g)</p>	<p>2</p> <p>Clear liquid</p> <p>400-900</p> <p>≤1</p> <p>100</p> <p>≤5</p>
<b>Packing</b>	<p>Net weight 50KG plastic bucket and net weight 200KG iron drum</p>	
<b>Storage conditions</b>	<p>Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 °C, storage conditions under normal conditions for at least 6 months.</p>	
<b>Use matters</b>	<p>Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.</p>	